

Vapotherm Transfer Unit

Hi-VNI™ on the GO₂

Ambulate and **Transfer** patients
without compromising
respiratory support.

- Maintain flow rate, temperature, and humidification levels
- Seamless transition from cylinders to wall gas
- Easy hot swap of patient circuit onto a stationary unit
- Alarms to alert user of therapy disruption



Vapotherm Transfer Unit

Technical Specifications

The Vapotherm Transfer Unit includes the Precision Flow roll stand, medical grade mobile power supply, Gas Manifold and E cylinder holder.

Ordering Information

Part Number: PF-VTU-NIST (Does not include Precision Flow)

Part Number: PF-UNIT-VTU-NIST (Includes Precision Flow)

Performance

The Vapotherm Transfer Unit (PF-VTU-NIST) allows the mobile delivery of Hi-VNI™ therapy within a hospital environment.

Tank gas supply: mobile run time will vary depending on the O₂/air blend and flow rate settings on the Precision Flow.

Sample estimates:

Flow Rate	FiO ₂	Approximate Time in Minutes
4	50%	170
4	100%	140
25	50%	27
25	21% or 100%	22
40	50%	17
40	21% or 100%	14

Battery life: Up to 1 hour.

Recharging time: Less than 3 hours, as displayed on the remote user interface



System Requirements

- 120V AC medical grade wall outlet (to charge battery)
- Oxygen E-Cylinder regulated to 50 psi
- Oxygen E-Cylinder regulator (not included)
- Air E-Cylinder regulated to 50 psi
- Air E-Cylinder regulator (included)
- Vapotherm Precision Flow